



北京环瑞商贸有限公司

BEIJING HUANRUI Co., Ltd

VP-440 雙由令球型逆止閥

True Union Ball Check Valve

- Minimum flow pressure: 5 PSI
- Install vertically or horizontally with flow direction arrow indication
- True union end connectors facilitate piping maintenance
- Good sealing function by ball check design
- 工作壓力：150 PSI
- 最低開啓壓力：5 PSI
- 依流向箭頭指示水平或垂直安裝
- 球體逆止設計，密閉性佳

| Type 品號 | Size 尺寸 | Standard 規格 | Material 材質 | Seat 墊座 | O-ring "O"環 | End type 接口 |
|------------|------------|----------------|----------------|----------------|----------------|------------------|
| VP-440 | 1/2"~2" | ANSI, JIS, DIN | PVC | EPDM, FPM, NBR | EPDM, FPM | Socket, Threaded |
| VP-441 | 1/2"~2" | ANSI, JIS, DIN | CPVC | EPDM, FPM, NBR | EPDM, FPM | Socket, Threaded |
| VP-444 | 1/2"~2" | ANSI, JIS, DIN | PP | EPDM, FPM, NBR | EPDM, FPM | Socket, Threaded |



| Nom. | SIZE | 15mm (1/2") | 20mm (3/4") | 25mm (1") | 40mm (1-1/2") | 50mm (2") |
|------|---------|----------------|----------------|--------------|------------------|--------------|
| | thd./in | NPT | 14 | 14 | 11.5 | 11.5 |
| | BSPT | 14 | 14 | 11 | 11 | 11 |
| JIS | d1 | 21.70 | 25.70 | 31.67 | 47.54 | 59.44 |
| | d2 | 22.30 | 26.30 | 32.33 | 48.46 | 60.56 |
| | l | 22.2 | 25.4 | 28.6 | 34.9 | 38.1 |
| ANSI | d1 | 21.23 | 26.57 | 33.27 | 48.11 | 60.17 |
| | d2 | 21.54 | 26.87 | 33.65 | 48.56 | 60.63 |
| | l | 22.22 | 25.4 | 28.58 | 34.93 | 38.1 |
| DIN | d1 | 20.1 | 25.1 | 32.1 | 50.1 | 63.1 |
| | d2 | 20.3 | 25.3 | 32.3 | 50.3 | 63.3 |
| | l | 16 | 19 | 22 | 31 | 38 |
| d | 16 | 20 | 25 | 40 | 50 | |
| D | 50 | 62 | 72 | 97 | 107 | |
| H | 89.3 | 111.5 | 129.3 | 167.6 | 191.4 | |

| NO. | PART | MATERIAL | Q'TY |
|-----|-----------|----------------|------|
| 1 | BODY | CPVC, UPVC, PP | 1 |
| 2 | UNION NUT | CPVC, UPVC, PP | 2 |
| 3 | CONNECTOR | CPVC, UPVC, PP | 2 |
| 4 | BALL | CPVC, UPVC, PP | 1 |
| 5 | GLAND | CPVC, UPVC, PP | 1 |
| 6 | SEAL | EPDM, FPM, NBR | 1 |
| 7 | O-RING | EPDM, FPM | 1 |

